

OFFICE OF THE REGULATED MARKET COMMITTEE, BARGARH

At – Goru Market , P.O. Bargarh, Dist. Bargarh, PIN-768028

(Invitation of Tender)

Tender Call Notice No. 28 / RMC Date. 12-11-2019

1. The Addl. District Magistrate-cum-Chairman, Regulated Market Committee, Bargarh invite rate quoted bid in sealed cover from the eligible authenticated Suppliers /Firms for establishment of fully electronic type (pitless kind) Weighbridge on turnkey basis with 60 M.T. capacity at Krushaka Bazar, RMC, Bargarh within two months from the finalization of the bid by signing of agreement by the bidder as per the **specification** given by the OSAM Board, Bhubaneswar vide letter no.1729 (66) dated 20.8.2019 attached with the notice and **terms & condition** as laid down vide OSAM Board, Bhubaneswar Notice No.2978 dated 19.10.2016 as given below. All bidders should submit the bid document in plain paper with proper format and with seal & signature to this office within the specified time period.

2. The details technical specification of fully electronic Weighbridge (pitless kind) of 60 M.T. capacity & the Weighbridge platform should be quality product of TATA /JINDAL / SAIL Steel with ancillary infrastructure on turnkey basis and AMC after one year of warranty should be quoted for three consecutive years.

3. The bidder should submit the rate quoted bid amount taking to the specification and follow the specification strictly at the time of supply and handed over the Weighbridge completed in all respect to the RMC within the specified time duration.


4. The bid in sealed envelope should be submitted in the office of the RMC, Bargarh before 3.00 P.M. of dated 20-11-2019 in Office Box or through Regd. Post which will reach in RMC office by 3.00 P.M. on dated 20-11-2019 . The RMC will not entertain any bid received after the time and date fixed. The bids will be opened at 11.00 A.M. on dt. 22-11-2019 .

5. The bidder, if so desire, may visit the site of installation of Weighbridge before submit the bid.

6. No advance amount will be paid to the supplier prior to completion of installation and handing over of Weighbridge.

7. The J.E./A.E. of OSAM Board, Bhubaneswar in charge of RMC, Bargarh will supervise the installation work and the bill amount will paid to the supplier after verification of technical specification by JE/ A.E.

8. At the time of submission of bid, the bidder must furnish his PAN card (Xerox) & last year I.T. return, GST certificate and latest return of GST & copy of valid license / authorization from Legal Metrology for supply of Weighbridge and his detail mail address with contact number etc.



9. Price quoted must be inclusive of all taxes and delivered at RMC destination point.

10. The bidder must be a manufacturer of electronic type weighbridge and must have obtained the approval of Legal Metrology Department and should be supplied minimum 25 (twenty five) numbers of electronic Weighbridge at different Market yards under Odisha Agricultural Marketing Board, Bhubaneswar. This is also mandatory for local MSME Unit.

11. The successful bidder should deposit the E.M.D. 2 % of bidding cost in shape of F.D./T.D. pledge in favour of Secretary of RMC, Bargarh with any Nationalized Bank and it will be released after handing over of Weighbridge complete in all respect.

12. 5 % of the bill amount will be deducted as security money which will be released to the bidder after one year from installation of Weighbridge on complying the defect if any detected within the time period.

13. Legal Metrology license like Manufacturing, Dealership, Repairing & Model approval issued by Directorate of Legal Metrology department, Government of India should attached with the Bid.

14. Standing suppliers should be done the stamping works by Legal Metrology Department for the first year & Test Weight will be provided by RMC.

15. Eligibility criteria

a). Local MSME bidder will be given preference and also preference will be given to the bidder who have installed minimum 25 nos. of Fixed Electronic Weighbridge at any of the RMC Market Yard or P.C. in Odisha. This is also mandatory for local MSME Unit in Odisha.

b) Service support of old Suppliers or good service provider to this office will be given an added advantage during negotiation.

The authority reserves the right to accept or reject any or all the bid without assigning any reason thereof.


Addl. District Magistrate-cum-
-Chairman, RMC, Bargarh
CHAIRMAN
Regulated Market Committee
BARGARH

(147)

TECHNICAL SPECIFICATION of fully Electronic weighbridge (Type – Pit less Kind)

40/50/60 MT capacity with ancillary infrastructure on Turn Key Basis with AMC

1. Electronic lorry weighbridge complete with platform, compression type load cells, digital indicator, recording and printing units.

1.1. Specification of Weighing System

- a. Capacity – 40/50/60 MT electronic static Road weigh bridge
- b. Class – III
- c. Verification scale interval (e) – 10 Kg.
- d. Accuracy – $\pm 0.05\%$ of the applied load.
- e. Memory – At least 10,000 trucks steering capacity
- f. Display – LED / Fluorescent
- g. Power supply – 230 volt Ac $\pm 10\%$; 50cps $\pm 5\%$ Single phase
- h. Provision of RS 232C/Rs 432 COM ports
- i. Operating temperature range – 0-55°C
- j. Security arrangement must be available with the Machine – Both hardware and software
- k. Six load cells digital type is preferable- Double ended shear beam /compression type ; capacity – 30MT (Minimum)
- l. Machine shall be delivered after certification by L.M.O.
- m. Working Software should be included

1.2. Plat form

The weighing platform of size 10m X3m shall be of chequered or antiskid plates of M.S. 12mm thickness with minimum 5 no of joists of 400 X 140 mm conforming to I.S. specification for 40/50/60 T weigh bridge . Minimum weight of platform (7 MT). The platform may be raised above the ground level for facilitating easy cleaning/maintenance (Max 1.0 Meter). The approach pavement (ramp) to platform shall be developed with cement concrete of M 25 grade on both side of the plat form. The gradient of the CC approach may be made limiting to 5% (1 in 20). Construction of concrete approach (CC of M25) to plat from on both side of plat form with a width of 5.5 mtr. as per the requirement of length at the site is under the scope of the bidder.

1.3. Specification of Digital Indicator

Capacity : Programmable up to 5 digits (Minimum)

Increment : Programmable 1.2 or 5 or their multiple

Display resolution : Maximum 1 in 10000

Operating Temperature : Maximum +55°C





Operating Humidity : Maximum 93% RH
Non Linearity : 0.016% of full scale or less

Repeatability : 0.016% of applied load

Internal Resolution : Should be adequate to handle the Accuracy level specified for the weighing system.

Decimal point selection : Selectable

Communication : Built in RS 232C.

Display type : LED Display / Fluorescent

Complete protection against electromagnetic and radio frequency interference.

1.4. U.P.S.

Capacity : 2 KVA / on line of reputed brand

1.5. CVT

3 KVA , Input : 130-270V, 50Hz+5% Output : 220+2%, 50Hz

1.6. Personal Computer

Desktop Configuration : Intel Corei5 Configuration

CPU : Inter core i5-3470, 3.2 GHz, 6 MB Cache or higher.

Chipset : Intel Q77 or better.

Bus Architecture : 4 PCI (PCI / PCI Express)

Memory : 4GB 1600 MHz DDR RAM with 32 GB Expandability

HDD : 500 GB 7200 rpm or higher.

Monitor : 47 cm or larger (18.5inch or larger) TFT/LED Digital Colour monitor TCO-05 certified.

Keyboard : 104 keys

Mouse : Optical with USB interface.

Ports : 6 USB Ports including 2 USB 3.0 Ports (with at least 2 in front), audio ports for micro phone and head phone in front.

Cabinet : Mini tower

DVD Drive : 8x or better DVD ROM drive



Networking Facility : 10/100/1000 n board integrated Network port with remote booting facility remote system installation, remote wake up, TPM enable 1.2 chip using any standard management software.

Operation Systems

(In Built) : Windows 8 professional / preloaded, as specified., with media and documentation and certificate of authenticity.

OS Certification : Windows 8 OS certification.

Power Management : Screen Blanking, Hard Disk and system idle mode in power on, Set-up password, power supply SMPS Surge protected.

Preloaded Software : Latest version of Mc Afee/Quick Heal/Norton Antivirus software.

Make : HP/DELL/LENOVO

1.7. Printer

Laser printer – Resolution (in dpi) : Mono 600 X 600, Paper size : A4, Print speed in PPM(A4size) : 25, Port : 1 USB, Memory (In MB) : NA, Network card 10/100 : Yes, Duplexing : Yes.

Make : HP/CANON/SAMSUNG

1.8. Software and interface requirements :

- The bidder needs to furnish relevant software interface for interfacing the weigh bridge with the computer systems for data transfer and other required operation such as calibration, testing etc. The systems must use standard serial / parallel / USB interface for communication. The selected bidder will have to ensure the integration of the W.B. to application software which is to be used by the user. The software associated with the weigh bridge should be able to provide standard interface so that the output from the weigh bridge can seamlessly be integrated with any software custom designed or otherwise to be deployed for management /regulation/administration of mineral transport and monitoring.
- The WB software must be user friendly and compatible with Windows – 7 or later versions for operation through GUI interface with total response time (data access and entry time) less than 20 seconds for any weightment transaction. Keyboard shortcuts must be available for the data entry fields with option for navigation using key board shortcut such as TAB key for maximum use of

[Handwritten signature]

